

ZYLOCK®

PERFORMANCE THREAD LOCKERS & SEALANTS



ZYLOCK CUSTOMERS SAY

"ZYLOCK, A GUARANTEED FAST AND RELIABLE SEAL, FIRST TIME, EVERY TIME!"

"ZYLOCK HAS SAVED ME HUGE AMOUNTS OF TIME."

"I NEVER LEAVE FOR A JOB WITHOUT ZYLOCK SEALANTS."

THE FULL RANGE & MERCHANDISING BOX



ALL SAFETY DATA SHEETS ARE AVAILABLE TO DOWNLOAD AT WWW.ZYLOCK.COM

ZYLOCK®

threadLOCK REMOVABLE 50ml ORDER CODE:PL010

Creates a vibration proof, sealed assembly.
Can be dismantled easily.

IDEAL FOR:
GUN & LANCE KIT ASSEMBLY
NUTS & BOLTS, STUDS, ETC.
Temp. Rating: -50° to +150° Centigrade. Colour: blue.



Retainer HIGH STRENGTH 50ml ORDER CODE:PL031

A high strength, fast curing retainer for securing all types of cylindrical parts. Reduces component fatigue by eliminating stresses within the assembly.

IDEAL FOR:
GEARS, PULLEYS, SPLINED SHAFTS
KEYWAYS, BEARINGS, ETC.
Temp. Rating: -55° to +155° Centigrade. Colour: green.



threadLOCK PERMANENT 50ml ORDER CODE:PL011

Creates a very strong, sealed assembly. Prevents corrosion and leakage, resists corrosive chemicals, fuels, and most industrial liquids and gases. Replaces double-nutting and welding.

IDEAL FOR:
REFRIGERATION
AIR CONDITIONING
GENERAL PRODUCTION LINE & PROCESS EQUIPMENT
Temp. Rating: -80° to +150° C. Colour: turquoise



Pipe Sealant 50ml ORDER CODE:PL041

Gives an instant seal but has a slow cure to allow for elbows, joints etc. to be realigned after assembly. Assists with lubrication during assembly.

IDEAL FOR:
SEALING ANY GAS, CHEMICAL, WATER OR STEAM PIPES
WITH COARSE THREADS UP TO 2 INCHES.
Temp. Rating: -55° to +150° Centigrade. Colour: white.



Hydraulic Seal 50ml ORDER CODE:PL020

Designed to secure and seal all types of hydraulic connections. Especially formulated not to clog up systems, suitable for up to 400 bar pressures. Giving an oil-tolerant, vibration proof seal. Easily dismantled.

IDEAL FOR:
PRESSURE LINES
THREADED COUPLINGS AND ADAPTORS
VALVES, COMPRESSION FITTINGS, ETC.
Temp. Rating: -55° to +150° Centigrade. Colour: brown.



Gasket Sealant POWERCAN 200ml ORDER CODE:PL050

Creates a gasket seal highly resistant to chemicals and temperature change. Eliminates leaks, reduces noise, absorbs vibration, seals and bonds assembly into a secure unit.

IDEAL FOR:
GEARBOXES, ENGINES, AND ANY OIL OR OTHER FLUID HOUSING.
Temp. Rating: -40° to +220° Centigrade. Colour: black.



Retainer REMOVABLE 50ml ORDER CODE:PL030

Designed to secure all types of cylindrical parts which require dismantling. Cures once confined between parts.

IDEAL FOR:
SECURING BEARINGS, SHAFTS, ETC.
Temp. Rating: -55° to +155° Centigrade. Colour: yellow.



PTFE Thread Seal Tape Conforms to British Standard BS7786 : 2006 Grade L ORDER CODE:PL040

SUITABLE FOR:
PORTABLE WATER AND OXYGEN

WRAS CERT No. 0506501
Made in England

